



SECTION A-A

**DYNAMIC FLUID CONTROL**  
 VALID FROM  
 Nov-20-12  
 UNTIL FURTHER NOTICE  
 SIGN: *D. Calldo*

© Copyright D.F.C.

<b>A3</b>	<b>Pro/E</b>
PINCH VALVE In Work	
MACHINING SYMBOLS TO ISO STANDARDS	
CASTING TOLERANCES UNLESS OTHERWISE SPECIFIED mm UNITS UP TO 75 ± 1.0 OVER 75 UP TO 150 ± 1.5 OVER 150 UP TO 250 ± 2.0 OVER 250 UP TO 500 ± 3.0 OVER 500 ± 4.0 ANGLES ± 1.0	MACHINING TOLERANCES UNLESS OTHERWISE SPECIFIED mm UNITS UP TO 120 ± 0.3 OVER 120 UP TO 300 ± 0.5 OVER 300 UP TO 1000 ± 0.8 OVER 1000 ± 1.2 ANGLES ± 0.1 DRILLED HOLES ± 0.1

1	0	30 DIA ROUND POM BLACK	ZMR03000PPOM	POLYACETAL
ITEM	QTY	DESCRIPTION	PART CODE	MATERIAL
REV. A	DATE: 26-Jul-12 04:01:22 PM	DONE BY:		
<b>AVENG MANUFACTURING DFC</b>		32 Lincoln Road, Benoni South P.O. BOX 5064, Benoni South, 1502, Gauteng, South Africa Tel: +27 11 748 0200 Fax: +27 11 421 2749		1 ST. ANGLE
THIS DRAWING AND DESIGN IS THE PROPERTY OF DYNAMIC FLUID CONTROL AND MUST NOT BE COPIED OR DISCLOSED TO ANY THIRD PARTY WITHOUT THE CONSENT OF THE COMPANY IN WRITING AND TO BE RETURNED UPON REQUEST.		SCALE: NTS	NAME	DATE
DRAWN		Calldo, Dennis	26-Jul-12 04:01:21 PM	
CHECKED		Calldo, Dennis	26-Jul-12 04:01:22 PM	
TITLE: DN025 STEM SCREW BUSHING			DRAWING No: / MODLE No: <b>BE025BHTPOM</b>	
SHEET 1 OF 1				