

# Data sheet

2 to 12 way 3.81mm PCB terminal block

**MB332-381M**

: Poles  
381 : Pitch 3.81mm  
332 : Standard  
MB : Type

**PCB Layout**

Current rating : 8Amp AC300V  
Insulation withstands volt : AC2000V min  
Insulation resistance : >2000MΩ DC500V  
Operation temperature : -40°C to +105°C  
Wire strip length : 4mm~5mm  
Wire range : 16~26 AWG  
Screw torque : 3.0 lb-inch

RoHS  
Compliant

Pitch : 3.81mm(0.150mch)					
Poles	A(mm)	A(mch)	Poles	A(mm)	A(mch)
2	7.62	0.300	15	57.15	2.250
3	11.43	0.450	16	60.96	2.400
4	15.24	0.600	17	64.77	2.550
5	19.05	0.750	18	68.58	2.700
6	22.86	0.900	19	72.39	2.850
7	26.67	1.050	20	76.20	3.000
8	30.48	1.200	21	80.01	3.150
9	34.29	1.350	22	83.82	3.300
10	38.10	1.500	23	87.63	3.450
11	41.91	1.650	24	91.44	3.600
12	45.72	1.800	25	95.25	3.750
13	49.53	1.950			
14	53.34	2.100			

CONFIRMED & ACCEPTED BY

文件管制

FEB 17, 2011

文管中心

	Material	Plating/Finish	Remark
1	Insulating body Polyamide 66(UL94V-0)		Green
2	Cage clamp Brass	Ni plated	
3	Terminal Brass	Tin plated	
4	Screw Steel	Ni plated	

PART NO.	MB332-381M	VERSION	C	CONFIRMED BY	<i>Widow</i>
SHEET OF	2/2	METRIC	MM	DRAWN BY	<i>Hsiang Ho</i>
				DATE	2011/02/17
				GENERAL MANAGER	<i>geller</i>

單據編號 : QR-0703-08 版次 : A版

